

Aluminum Fiber Optic Storage System

The aluminum Opti-Loop™ FOS for strand and messenger mounted cable is available in a variety of sizes. With more than one million units in service, Opti-Loop fiber storage systems lead the industry in quality and durability.

DESIGN FEATURES AND BENEFITS

- All aluminum construction with continuous welds at crossbars and ends.
- Each pair is individually boxed and includes stainless steel mounting bolts, nuts and washers.
- Fits all fiber cable up to 1.50" OD.
- Powder coat finish.
- Tie eyelets designed to accommodate both stainless steel and tie wrap securing methods.
- Radius ends to ensure no sharp corners.
- Outward facing channel and minimal surface area minimizes stress and ice loading.



Ordering Information

Catalog Number	Size (Inches)	Length (Inches)	Outside Diameter (Inches)
FOS10TMK	10.2	23	11.4
FOS1TMK	12.2	26	13.4
FOS2TMK*	12.2	26	13.4
FOS3TMK	16.2	31	17.7
FOS3DTMK*	16.2	31	17.7
FOS4TMK	18.2	33	19.7
FOS5TMK*	18.2	33	19.8
FOS6TMK	20.2	34	21.4
FOS24TMK	24.0	38	25.4
FOS30TMK	30.0	44	31.4

*Indicates multi-wrap unit