

Length (in.)	Color	Connectors	Cable
09	W <i>(white)</i>	Compression	RG-59
18	BK <i>(black)</i>	SNS <i>(Thomas & Betts Snap N Seal)</i>	C1V <i>(Comm Scope F5967BVV)</i>
30	BE <i>(Beige)</i>	UE <i>(Gilbert Ultra Ease)</i>	C5V <i>(Commscope F59SSVV)</i>
36	N <i>(Neutral)</i>	US <i>(Gilbert Ultra Seal - all brass)</i>	C3V <i>(Comm Scope F5995BVV)</i>
48		EX <i>(PPC)</i>	B2 <i>(Belden 9104 67%)</i>
60		EXL <i>(PPC long)</i>	B3 <i>(Belden 9108 95%)</i>
72		SLC <i>(Holland - all brass)</i>	B14 <i>(Belden Quad Shield 1186A)</i>
96		SLCO <i>(Holland - all brass with o ring)</i>	RG-6
108		Crimp	C9V <i>(Comm Scope F660BVV)</i>
120		CHI <i>(Thomas & Betts crimp - gold)</i>	C7V <i>(Comm Scope F6SSVV)</i>
132		CH <i>(Thomas & Betts Snap N Seal)</i>	C11V <i>(Comm Scope F6TSVV)</i>
144		AHS <i>(Gilbert)</i>	C12V <i>(Comm Scope F677TSVV)</i>
180		AG <i>(Generic - gold)</i>	B5 <i>(Belden 9116 60%)</i>
		AS <i>(Generic - nickle)</i>	B20 <i>(Belden 1613A 77% TRI)</i>
		PPCU <i>(Indoor crimp)</i>	B15 <i>(Belden 1189A Quad Shield)</i>
		PPCSU <i>(Crimp with gel)</i>	
		PPCSUV <i>(Crimp with gel & O-ring)</i>	

Example: **36 BK SNS C1V** - (36 inch, Black Jumper with T&B Snap-N-Seal Connectors and CommScope F5967 BVV Cable)