PRIMEX Product Specification Sheet

PRODUCT MODEL CODE

P750FCC Dual Fiber Transition

1. PRODUCT SUMMARY

The Primex P750FCC dual fiber transition/ slack storage for FTTH applications gives you the flexibility to customize the box to meet your deployment needs on your project. The compact design features up to 2 SC/APC adapters, a dual bulkhead, flat grommet and a 1" conduit adapter

2. PRODUCT DIMENSIONS

Inside H 9.1"/W: 6.1"/D: 3.1"

3. FEATURES & BENEFITS

- Ideal for FTTx and BroadBand markets.
- Up to 2 SC/APC fiber adapters.
- Dual bulkhead
- Grommet and a 1" conduit adapter.
- 3 Hurricane Clips for slack storage.
- Weather proof design with optional NEMA 4X.
- Dual snap locks to ensure lid seals to base.
- Mounting hole pattern.
- Security screw grounding post available.
- Allow 24/7 secure access by a service technician with the available override or F81 locking mechanism.
- Deploy quickly and easily with external wall and pole mounting brackets that eliminate the need to drill through box.

4. CONFIGURATIONS

SC 125-1299 Description P750 2 Fiber/Slack Storage w/SC/APC Adapters

FOR MORE INFORMATION CONTACT:

20160 92A Avenue Langley BC V1M 3A4 Canada 1.604.881.7875 1.877.881.7875 9 info@primexfits.com









