

910CL OPTICAL FIBER CLEAVER

For use with the 910FS Fusion Splicer



FAST.

Easy to set up. Cleaved fiber remains in the adapter ready for splicing in the 910FS.

ACCURATE.

Precision-engineered blades accurately cleave fibers for minimal loss.

RELIABLE.

Field tested to perform. Dust bin to safely collect end cuts.

910CL OPTICAL FIBER CLEAVER


FOR PRODUCT VIDEOS, DEMONSTRATIONS AND MORE, SCAN THIS QR CODE OR VISIT:

www.youtube.com/GreenleeDEMO



FEATURES

- Accurate Cleaves. Cleave multi-mode and single-mode fiber optic cables.
- Long Life. Blades rotate for longer life over 16,000 cleaves.
- Adaptable. Supports 250um, 900um fibers.
- Fast. For use with the 910FS Optical Fusion Splicer for maximum speed and efficiency.
- Dust bin. Safely collects end cuts during cleaving process.



SPECIFICATIONS

APPLICABLE FIBERS	SM (G.652); MM (G.651); DS (G.653); NZDS (G.655); BIF (G.657)	
FIBER CLEAVED LENGTH	10mm	
CLADDING DIAMETER	125µm	
COATING DIAMETER	0.25 mm and 0.9 mm	
FIBER COUNT	Single	
CLEAVING ANGLE	≤ 1.5° 16,000 Cleaves 0.56 lbs (255 g) 2.29 x 2.17 x 1.89" (58 x 55 x 48 mm)	
BLADE LIFE		
WEIGHT		
DIMENSIONS (HxWxD)		



ORDERING INFORMATION

CAT NO.	UPC NO.	DESCRIPTION
910CL	01331	Optical Fiber Cleaver
910CL-BLADE	16403	Cleaving Wheel
910FS	01328	Optical Fusion Splicer
910FS-250	01332	250µm Adapter
910FS-900	01333	900µm Adapter

CAT NO.	UPC NO.	DESCRIPTION
910FS-SOC-SC-LC	01335	Adapter, Splice-On Connector, SC & LC
910FS-SOC-ST-FC	02401	Adapter, Splice-On Connector, ST & FC
PA1171	12225	Buffer Strippers
45589	45589	Buffer Strippers
45483A	02523	Kevlar Cutters

DISTRIBUTOR INFORMATION:













