

VIKIMATIC STEEL PIPE

B.T.C. - Black Threaded & Coupled. **G.T.C.** - Galvanized Threaded & Coupled.

WEIGHT TABLE OF ELECTRICAL RESISTANCE WELDED (ERW) STEEL PIPE

Nominal Size in	Outside Diameter		Wall Thickness		Nominal Weight						Weight Class	Sch. No.
	in	mm	in	mm	Plain Ends			Threads & Couplings				
					lb/ft	kg/ft	kg/m	lb/ft	kg/ft	kg/m		
1/2	0.840	21.3	0.109	2.77	0.85	0.39	1.27	0.85	0.39	1.27	STD	40
			0.147	3.73	1.09	0.49	1.62	1.09	0.49	1.62	XS	80
3/4	1.050	26.7	0.113	2.87	1.13	0.51	1.69	1.13	0.51	1.68	STD	40
			0.154	3.91	1.47	0.67	2.20	1.48	0.67	2.20	XS	80
1	1.315	33.4	0.133	3.38	1.68	0.76	2.50	1.68	0.76	2.50	STD	40
			0.179	4.55	2.17	0.98	3.24	2.18	0.99	3.24	XS	80
1-1/4	1.660	42.2	0.140	3.56	2.27	1.03	3.39	2.28	1.03	3.39	STD	40
			0.191	4.85	3.00	1.36	4.47	3.02	1.37	4.49	XS	80
1-1/2	1.900	48.3	0.145	3.68	2.72	1.23	4.05	2.73	1.24	4.06	STD	40
			0.200	5.08	3.63	1.65	5.41	3.66	1.66	5.45	XS	80
2	2.375	60.3	0.154	3.91	3.65	1.66	5.44	3.68	1.67	5.48	STD	40
			0.218	5.54	5.02	2.28	7.48	5.07	2.30	7.55	XS	80
2-1/2	2.875	73.0	0.203	5.16	5.79	2.63	8.63	5.82	2.64	8.66	STD	40
			0.276	7.01	7.66	3.47	11.41	7.73	3.51	11.50	XS	80
3	3.500	88.9	0.216	5.49	7.58	3.44	11.29	7.62	3.46	11.34	STD	40
			0.300	7.62	10.25	4.65	15.27	10.33	4.69	15.37	XS	80
3-1/2	4.000	101.6	0.226	5.74	9.11	4.13	13.57	9.20	4.17	13.69	STD	40
			0.318	8.08	12.50	5.67	18.63	12.63	5.73	18.80	XS	80
4	4.500	114.3	0.188	4.78	8.66	3.93	12.91	-	-	-	-	-
			0.237	6.02	10.79	4.89	16.07	10.98	4.94	16.21	STD	40
			0.337	8.56	14.98	6.80	22.32	15.17	6.88	22.58	XS	80
5	5.563	141.3	0.188	4.78	10.79	4.89	16.07	-	-	-	-	-
			0.258	6.55	14.62	6.63	21.77	14.81	6.72	22.04	STD	40
			0.375	9.53	20.78	9.43	30.97	21.09	9.57	31.39	XS	80
			0.500	12.70	27.04	12.27	40.20	-	-	-	-	-
6	6.625	168.3	0.188	4.78	12.92	5.86	19.27	-	-	-	-	-
			0.250	6.35	17.02	7.72	25.36	-	-	-	-	-
			0.280	7.11	18.97	8.60	28.26	19.18	8.70	28.54	STD	40
			0.432	10.97	28.57	12.96	42.56	28.89	13.10	42.99	XS	80
8	8.625	219.1	0.188	4.78	16.94	7.68	25.26	-	-	-	-	-
			0.250	6.35	22.36	10.14	33.31	-	-	-	-	20
			0.277	7.04	24.70	11.20	36.81	25.55	11.59	38.02	-	30
			0.322	8.18	28.55	12.95	42.55	29.35	13.31	43.68	STD	40
			0.406	10.31	35.64	16.17	53.08	-	-	-	-	60
			0.500	12.70	43.36	19.68	64.64	43.90	19.91	65.33	XS	80
10	10.750	273.1	0.188	4.78	21.21	9.62	31.63	-	-	-	-	-
			0.219	5.56	24.63	11.17	36.68	-	-	-	-	-
			0.250	6.35	28.04	12.72	41.77	-	-	-	-	20
			0.279	7.09	31.20	14.15	46.51	32.75	14.86	48.74	-	-
			0.365	9.27	40.48	18.36	60.31	41.85	18.98	62.28	STD	40
0.500	12.70	54.74	24.83	81.55	55.82	25.32	83.07	XS	60			
12	12.750	323.9	0.219	5.56	29.31	13.29	43.65	-	-	-	-	-
			0.250	6.35	33.38	15.14	49.73	-	-	-	-	20
			0.330	8.38	43.77	19.85	65.20	45.45	20.62	67.64	-	30
			0.375	9.53	49.56	22.48	73.88	51.15	23.20	76.12	STD	-
			0.406	10.31	53.52	24.28	79.73	-	-	-	-	40
			0.500	12.70	65.42	29.67	97.46	66.71	30.26	99.28	XS	-

It is purchaser's responsibility to inspect all material delivered at time of delivery. The seller makes no warranty, expressed or implied, that the material is fit for any particular purpose whatsoever unless specifically written in detail.